

HUURRE ECO[®]

MINI CO2 Refrigeration unit

Used for cold rooms, retail cabinets, freezers and comfort cooling (DX)

Standard design:

- Semi-hermetic compressor (400V 50Hz)
- Electronic high pressure valve
- Electronic receiver valve
- Filters in suction and liquid lines
- Pressostats for compressor (LP, IP, HP)
- Electrical panel with start- and regulation equipment
- Inverter (35...60Hz)
- Suction/ liquid hx
- Safety valves (LP, IP, HP)
- Flexible installation, can be installed against a wall

Options:

- Air gas cooler
- Liquid cooled gas cooler
- Evaporator for cooling brines (MT)
- Enclosure for outside installation , sound insulation



Huurre Eco MINI

Huurre Eco Model 60/60/120 bar	Number of compressors/mod	Dimensions (width x depth x height) + max. 80 mm för feet	Weight	Freezing capacity LT -29C/+32C/kW	Cooling MT-7C/+32C	Required Condensing kW	Supply Amps
ECO MINI LT 2,5...4,9	LT/CD 700 H-1	790 x 590 x 1400	350	2,9...4,9		9,7	3 x 16
ECO MINI LT 5,2...10,4	LT/CD 1300 H-1	790 x 590 x 1400	395	6,1...10,4		20,3	3 x 25
ECO MINI MT 2,6...5,3	MT/CD 350 H-1	790 x 590 x 1400	305		3,1...5,3	8,0	3 x 16
ECO MINI MT 6,3...12,7	MT/CD 700 H-1	790 x 590 x 1400	350		7,4...12,7	18,5	3 x 25

HUURRE
VALUE-ADDED REFRIGERATION